

64265 HLX

Low-voltage halogen lamps without reflector



Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)

Product family benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

Product family features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)



Product datasheet

Technical data

Product information

Order reference	64265 HLX
-----------------	-----------


Electrical data

Nominal voltage	6 V
Nominal wattage	30.00 W

Photometrical data

Color temperature	3200 K
Nominal luminous flux	765 lm
Color rendering index Ra	100

Dimensions & weight



Diameter	9 mm
Length	31.0 mm
Light center length (LCL)	19.5 mm
Filament length	1.60 mm
Illuminated field	1.6*1.6 mm ²
Filament diameter	1.6 mm

Lifespan

Lifespan	100 h
----------	-------

Additional product data

Base (standard designation)	G4
Minimum diameter of lamp enclosure	9 mm

Product datasheet

Capabilities

Burning position	Any
Application	Other

Country specific categorizations

Order reference	64265 HLX
-----------------	-----------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4008321107053 4055462167620
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321107053	OSRH64265HLX	-	-	-
4008321107053	OSRH64265HLX	-	-	-