

64292 XIR

Low-voltage halogen lamps without reflector



Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)

Product family benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

Product family features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)



Product datasheet

Technical data

Product information

Order reference	64292
-----------------	-------


Electrical data

Nominal voltage	22.8 V
Nominal wattage	150.00 W

Photometrical data

Color temperature	3250 K
Nominal luminous flux	6000 lm
Color rendering index Ra	100

Dimensions & weight



Diameter	14.0 mm
Length	44.0 mm
Light center length (LCL)	30.0 mm ¹⁾
Filament length	2.80 mm
Illuminated field	2.8*6.7 mm ²
Filament diameter	6.7 mm

¹⁾ ±0.3 mm

Lifespan

Lifespan	600 h
----------	-------

Additional product data

Base (standard designation)	G6.35
Minimum diameter of lamp enclosure	14 mm

Product datasheet

Capabilities

Burning position	s90
Application	Other

Country specific categorizations

Order reference	64292
-----------------	-------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4008321330598
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321330598	OSRH64292XIR	-	-	-
4008321330598	OSRH64292XIR	-	-	-