
EFR-5/X 64620 HLX 150W 15V 20/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54211
Product Name	EFR5X64620HLX 15V 20/CS 1/SKU
Ordering Abbreviation	EFR-5/X 64620 HLX 150W 15V 20/CS 1/SKU
Brand Name	OSRAM
Family Brand Name	XENOPHOT (HLX)
General Description	150 watt, tungsten halogen, low to medium voltage with reflector
Application	Projector - 8mm
LIF Code	A1/232
Product Remark	- p (Operating Position) = Horizontal

Electrical data

Nominal Wattage	150 W
Nominal Voltage	15 V
Type of Current	AC

Light technical data

Working Distance a (in)	1.259 in
Working Distance a (mm)	32 mm
Average Rated Life	500 h

Physical attributes

Base	GZ6.35 Bipin
Bulb Shape	T11,5
Maximum Overall Length (in)	1.654 in
Maximum Overall Length (mm)	42 mm
Length l (in)	1.654 in
Length l (mm)	42 mm
Length l max. (in)	1.654 in
Length l max. (mm)	42 mm
Diameter d (in)	1.969 in
Diameter d (mm)	50.00 mm
Filament	C-8
Reflector Coating	50.00

Additional product data