

8100 30W 5V 100/CS 1/SKU



Product features and benefits

- Dependable quality
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	76321
Product Name	8100 5V 100/CS 1/SKU
Ordering Abbreviation	8100 30W 5V 100/CS 1/SKU
Brand Name	OSRAM
General Description	5A, nonhalogen, low voltage
Application	Projector
LIF Code	F/74
Product Remark	- s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	30 W
Nominal Voltage	5 V
Type of Current	AC

Light technical data

Color Rendering Index	100
Average Rated Life	600 h


Physical attributes

Base	E14
Bulb Shape	-
Maximum Overall Length (in)	2.535 in
Maximum Overall Length (mm)	65 mm
Length l (in)	2.535 in
Length l (mm)	65 mm
Length l max. (in)	2.535 in
Length l max. (mm)	65 mm
Diameter d (in)	1.378 in
Diameter d (mm)	35.00 mm
Distance a (in)	1.755 in
Distance a (mm)	45 mm
Filament Dimensions Length (in)	0.0780 in
Filament Dimensions Length (mm)	2 mm
Filament Dimensions Width (in)	0.078 in
Filament Dimensions Width (mm)	2 mm

Product datasheet

Additional product data

Operating Position	s 105
Total surface inside 1: appearance (cold)	Clear
Class	C (gas)



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
76321	4050300342122	Folding box (SKU)	1	1.4 in x 1.4 in x 2.7 in	
76321	4050300342139	Shipping box (Case)	100	14.4 in x 6.5 in x 7.5 in	4 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.