



# Blue (/52) - PL-L, PL-S

## PL-L 18W/52/4P 1CT/25

By emitting light almost entirely within the 400 to 500 nm bandwidth and peaking at 450 nm, Philips PL-L/PL-S color 52 lamps have no radiation from the short wave UVB. waveband. They are therefore suitable to be used in systems for applications such as Agriculture and Neonatal Jaundice Phototherapy

### Warnings and Safety

- lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take them to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Photobiological safety – IEC 62471 - Risk Group 2. CAUTION - Possibly hazardous optical radiation emitted from these products.

### Product data

General Information	
Cap-Base	2G11 [2G11]

Light Technical	
Color Code	52
Luminous Flux	330 lumen
Chromaticity Coordinate X (Nom)	155
Chromaticity Coordinate Y (Nom)	75

Operating and Electrical	
Power Consumption	17.5 W
Lamp Current (Nom)	0.375 A
Voltage (Nom)	57 V
Voltage (Nom)	57 V

Mechanical and Housing	
Bulb Shape	2xT16

Approval and Application	
Mercury (Hg) Content (Nom)	4.4 mg


Product Data	
Full product code	872790080517800
Order product name	PL-L 18W/52/4P 1CT/25
Order code	927904105206
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927904105206
Full product name	PL-L 18W/52/4P 1CT/25
EAN/UPC - Case	8727900805185

## Blue (/52) - PL-L, PL-S

EAN/UPC - Product/Case

8727900805178

### Dimensional drawing



Product	D1 (max)	D (max)	A (max)	B (max)	C (max)
PL-L 18W/52/4P 1CT/25	18 mm	39 mm	188.2 mm	214 mm	220.6 mm

