



## Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

## Areas of application

- Airfield lighting

## Product datasheet

### Technical data

#### General product information

Application	Airfield/Airport
-------------	------------------

#### Electrical data

Nominal Wattage	40 W
Current (A)	6.6 A
Type of Current	AC

#### Light technical data

Luminous Intensity (cd)	12700 cd
Color Rendering Index	100
Average Rated Life	1000 h

#### Physical attributes

Base	LEADS W/FEMALE ROUND CONNECTOR
Bulb Shape	MR11
Maximum Overall Length (in)	1.457 in
Maximum Overall Length (mm)	37 mm
Diameter d (in)	1.390 in
Diameter d (mm)	35.30 mm

#### Additional product data

Operating Position	Any
Lamp Type	SINGLE ENDED

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
	4008321104731	Folding box (SKU)	1	1.3 in x 1.3 in x 2 in	0.1 lb
	4008321104748	Shipping box (Case)	20	5.2 in x 7.5 in x 3.2 in	1 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.